



Tel: 514-956-7503
Fax: 514-956-7504
Internet: www.megs.ca
Email : support@megs.ca

Montreal	St-Laurent	Tel : 514-956-7503	Fax : 514-956-7504
Ottawa	Nepean	Tel : 613-226-4228	Fax : 613-226-4229
Quebec	Quebec	Tel : 418-834-7447	Fax : 418-834-3774

MSDS: Argon Compressed

PRODUCT INFORMATION

PRODUCT: Argon
TRADE NAME: Argon
CHEMICAL NAME: Argon
SYNONYMS: Argon Compressed
FORMULA: Ar
CHEMICAL FAMILY: Inert Gas or Rare Gas
SUPPLIER'S NAME: MEGS Inc.
SUPPLIER'S ADDRESS: 2675 De Miniac
Ville St-Laurent, Qc, H4S 1E5
EMERGENCY PHONE NUMBER: (514) 956-7503
MOLECULAR WEIGHT: 39.95
PRODUCT USE: Various
PRODUCT IDENTIFICATION UN 1006
NUMBER:

HAZARDOUS INGREDIENTS

CHEMICAL ID	CONCENTRATION	CAS #	LD(50)	LC(50)
Argon	100%	7440-37-1	None	None

PHYSICAL DATA

PHYSICAL STATE: Gas
APPEARANCE: Colorless gas
ODOR: Odorless
ODOR THRESHOLD: Not applicable
SPECIFIC GRAVITY (H₂O = 1): See Vapor Density (air = 1)
VAPOR PRESSURE: Not applicable (gas)
VAPOR DENSITY (air = 1): 1.380

EVAPORATION RATE: Not applicable (gas)
BOILING POINT: -185.86°C
FREEZING POINT: -189.37°C
pH: Not applicable (gas)
GAS DENSITY: 1.687 kg/m³ @ 15°C, 101.3 kPa
COEFFICIENT OF WATER/OIL @ 15°C, Bunsen Coefficient =
DISTRIBUTION: 0.0375

FIRE OR EXPLOSION HAZARD

CONDITIONS OF FLAMMABILITY: Nonflammable gas
MEANS OF EXTINCTION: Nonflammable gas
FLASHPOINT AND METHOD OF DETERMINATION: Nonflammable gas
UPPER EXPLOSION LIMIT (% BY VOL): Nonflammable gas
LOWER EXPLOSION LIMIT (% BY VOL): Nonflammable gas
AUTO-IGNITION TEMPERATURE: Nonflammable gas
FLAMMABILITY CLASSIFICATION: Nonflammable gas
HAZARDOUS COMBUSTION PRODUCTS: Nonflammable gas
EXPLOSION DATA: Nonflammable gas
SENSITIVITY TO STATIC DISCHARGE: Nonflammable gas

REACTIVITY DATA

CHEMICAL STABILITY: Stable
INCOMPATIBLE MATERIALS: None
CONDITIONS OF REACTIVITY: Non-reactive
HAZARDOUS DECOMPOSITION PRODUCTS: None

TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY:

SKIN CONTACT: None

SKIN ABSORPTION: None

EYE: None

INHALATION: Argon is defined as a simple asphyxiant. Oxygen level should be maintained at greater than 18 molar percent at normal atmospheric pressure which is equivalent to a partial pressure of 135 mm Hg. (ACGIH 1995-1996).

INGESTION: No

ACUTE OVER EXPOSURE EFFECTS: See Inhalation, above.

CHRONIC OVER EXPOSURE EFFECTS: None

EXPOSURE LIMITS: See Inhalation, above.

IRRITANCY OF PRODUCT: None

SENSITIZATION TO MATERIAL: None

CARCINOGENICITY, REPRODUCTIVE EFFECTS: None

TERATOGENICITY, MUTAGENICITY: None

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: None

PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Safety goggles and safety shoes.

SPECIFIC ENGINEERING CONTROLS: Argon is noncorrosive and may be used with any common structural material.

LEAK AND SPILL PROCEDURES: EVACUATE ALL PERSONNEL FROM AFFECTED AREA.

Use appropriate protective equipment. If leak is on container or container valve, contact the closest MEGS location.

WASTE DISPOSAL: Do not attempt to dispose of waste or unused quantities. Return in the shipping container properly labeled, with any valve outlet plugs or caps secured and valve protection cap in place to MEGS for proper disposal. For emergency disposal, contact the closest MEGS location.

HANDLING PROCEDURES AND EQUIPMENT: USE ONLY IN WELL-VENTILATED AREAS.

Valve protection caps must remain in place unless container is secured with valve outlet piped to point of use. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinders to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Do not tamper with (valve) safety device. Close valve

after each use and when empty.

STORAGE REQUIREMENTS: Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first-out" inventory system to prevent full cylinders from being stored for excessive periods of time.

TDG CLASSIFICATION: 2.2

WHMIS CLASSIFICATION: A

SPECIAL SHIPPING INFORMATION: Always secure cylinders in an upright position before transporting them. NEVER transport cylinders in trunks of vehicles, enclosed vans, truck cabs or in passenger compartments. Transport cylinders secured in open flatbed or in open pick-up type vehicles.

FIRST AID MEASURES

SPECIFIC FIRST AID PROCEDURES: PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO ARGON. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.

INHALATION: Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, given assisted resuscitation and supplemental oxygen. Medical assistance should be sought immediately.

EYE CONTACT: Not applicable

SKIN CONTACT: Not applicable

PREPARATION INFORMATION

PREPARED BY: Safety Department

DATE PREPARED: 09/01/1999

LAST REVISION DATE: 04/01/2008

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, MEGS INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.