



Tel: 514-956-7503
Fax: 514-956-7504
Internet: www.megs.ca
Email : support@megs.ca

Montreal	St-Laurent	Tel : 514-956-7503	Fax : 514-956-7504
Ottawa	Nepean	Tel : 613-226-4228	Fax : 613-226-4229
Quebec	Quebec	Tel : 418-834-7447	Fax : 418-834-3774

MSDS: Ethyl Acetylene

PRODUCT INFORMATION

PRODUCT: Ethyl Acetylene

TRADE NAME: Ethyl Acetylene or 1-Butyne

CHEMICAL NAME: Ethyl Acetylene or 1-Butyne

SYNONYMS: Butyne

FORMULA: C₄H₆

CHEMICAL FAMILY: Alkyne

SUPPLIER'S NAME: MEGS Inc.

SUPPLIER'S ADDRESS: 2675 De Miniac
Ville St-Laurent, Qc, H4S 1E5

EMERGENCY PHONE NUMBER: (514) 956-7503

MOLECULAR WEIGHT: 54.09

PRODUCT USE: Various

**PRODUCT IDENTIFICATION UN 2452
NUMBER:**

HAZARDOUS INGREDIENTS

CHEMICAL ID	CONCENTRATION	CAS #	LD(50)	LC(50)
	100%			
Ethyl Acetylene		107-00-6	None	None

PHYSICAL DATA

PHYSICAL STATE: Liquid and gas under pressure

APPEARANCE: Colorless gas and liquid with acetylenic odor

ODOR: See above

ODOR THRESHOLD: Unknown

SPECIFIC GRAVITY (H₂O = 1): Liquid at Boiling Point = 0.650

VAPOR PRESSURE: @ 15°C = 132 kPa
VAPOR DENSITY (air = 1): 1.94
EVAPORATION RATE: Unknown
BOILING POINT: 8.08°C
FREEZING POINT: -125.72°C
pH: Unknown
GAS DENSITY: 2.32 kg/m³ @ 15°C, 101.3 kPa
COEFFICIENT OF WATER/OIL @ 15°C, Bunsen Coefficient = 2.0
DISTRIBUTION:

FIRE OR EXPLOSION HAZARD

CONDITIONS OF FLAMMABILITY: Flammable in air

MEANS OF EXTINCTION: Water, carbon dioxide, dry chemical.
"Stop flow of gas before extinguishing fire".

FLASHPOINT AND METHOD OF DETERMINATION: Unknown

UPPER EXPLOSION LIMIT (% BY VOL): Stoichiometric combustion in air
LOWER EXPLOSION LIMIT (% BY VOL): Stoichiometric combustion in air

AUTO-IGNITION TEMPERATURE: Unknown

FLAMMABILITY CLASSIFICATION: Class 1, group not specified

HAZARDOUS COMBUSTION PRODUCTS: None

EXPLOSION DATA: Yes with halogens

SENSITIVITY TO STATIC DISCHARGE: Unknown

REACTIVITY DATA

CHEMICAL STABILITY: Yes, possible isomerization above 200°C

INCOMPATIBLE MATERIALS: Oxidizers, halogens, halogenated compounds

CONDITIONS OF REACTIVITY: Heat

HAZARDOUS DECOMPOSITION PRODUCTS: None

TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY:

SKIN CONTACT: None

SKIN ABSORPTION: None

EYE: None

INHALATION: Moderate concentrations so as to exclude an adequate supply of oxygen to the lungs causes dizziness, drowsiness, and eventual unconsciousness. It has been reported to act as a narcotic.

INGESTION: None

ACUTE OVER EXPOSURE EFFECTS: Has been reported that breathing high concentrations causes a narcotic or anesthetic effect; however, the major property is the exclusion of an adequate supply of oxygen to the lungs.

CHRONIC OVER EXPOSURE EFFECTS: None reported

EXPOSURE LIMITS: No TWA is listed (ACGIH 1995-1996). It should be defined as a simple asphyxiant. Oxygen levels should be maintained at greater than 18 molar percent at normal atmospheric pressure which is equivalent to a partial pressure of 135 mm Hg.

IRRITANCY OF PRODUCT: None known

SENSITIZATION TO MATERIAL: None

CARCINOGENICITY, REPRODUCTIVE EFFECTS: None

TERATOGENICITY, MUTAGENICITY: None

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: Acetylene

PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Plastic or rubber gloves. Safety goggles or safety glasses. Safety shoes, safety shower.

SPECIFIC ENGINEERING CONTROLS: Most metals are compatible with ethyl acetylene. It forms explosive acetylide compounds with copper, mercury, silver and brasses with more than 66% copper.

LEAK AND SPILL PROCEDURES: EVACUATE ALL PERSONNEL FROM PERSONNEL AREA.

Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is on container or

container valve, contact the closest MEGS location.

WASTE DISPOSAL: Do not attempt to dispose of waste or unused quantities. Return in the shipping container properly labeled, with any valve outlet plugs or caps secured and valve protection cap in place to MEGS for proper disposal. For emergency disposal, contact the closest MEGS location.

HANDLING PROCEDURES AND EQUIPMENT: USE ONLY IN WELL-VENTILATED AREAS.

Valve protection caps must remain in place unless container is secured with valve outlet piped to the point of use. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Do not tamper with (valve) safety device. Close valve after each use and when empty.

STORAGE REQUIREMENTS: Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first out" inventory system to prevent full cylinders being stored for excessive periods of time. Post "No Smoking or Open Flames" signs in the storage or use area. There should be no sources of ignition in the storage or use area.

TDG CLASSIFICATION: 2.1

WHMIS CLASSIFICATION: A, B

SPECIAL SHIPPING INFORMATION: Always secure cylinders in an upright position before transporting them. NEVER transport cylinders in trunks of vehicles, enclosed vans, truck cabs or in passenger compartments. Transport cylinders secured in open flatbed or in open pick-up type vehicles.

FIRST AID MEASURES

SPECIFIC FIRST AID PROCEDURES: PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO ETHYL ACETYLENE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS AND BE COGNIZANT OF EXTREME FIRE AND EXPLOSION HAZARD.

INHALATION: Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, given assisted resuscitation and supplemental oxygen. Medical assistance should be sought immediately.

EYE CONTACT: PERSONS WITH POTENTIAL EXPOSURE TO ETHYL ACETYLENE SHOULD NOT WEAR CONTACT LENSES.

Flush contaminated eye(s) with copious quantities of water. Part eyelids to assure complete flushing. Continue for a minimum of 15 minutes.

SKIN CONTACT: Flush affected area with copious quantities of water. Remove affected clothing as rapidly as possible.

PREPARATION INFORMATION

PREPARED BY: Safety Department

DATE PREPARED: 01/01/1999

LAST REVISION DATE: 05/21/2002

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, MEGS INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.